

MODEL	Control	Digits	Height character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-203X			ALPHANUMERICAL LED. INDOORS			RS-232/485	
DT-203/2SX	Serial	20	30	2	1	615x170x120	Yes
DT-203/2DX	Serial	20	30	2	2	615x170x120	Yes
DT-203/4SX	Serial	20	30	4	1	615x317x120	Yes
DT-203/4DX	Serial	20	30	4	1	615x317x120	Yes
DT-203/6SX	Serial	20	30	6	1	615x464x120	Yes
DT-203/6DX	Serial	20	30	6	1	615x464x120	Yes
DT-203/8SX	Serial	20	30	8	1	615x611x120	Yes
DT-203/8DX	Serial	20	30	8	1	615x611x120	Yes

DT-203P			ALPHANUMERICAL LED. INDOORS			BINARY	
DT-203/2SP	Binary	20	30	2	1	615x170x120	Yes
DT-203/2DP	Binary	20	30	2	2	615x170x120	Yes
DT-203/4SP	Binary	20	30	4	1	615x317x120	Yes
DT-203/4DP	Binary	20	30	4	1	615x317x120	Yes
DT-203/6SP	Binary	20	30	6	1	615x464x120	Yes
DT-203/6DP	Binary	20	30	6	1	615x464x120	Yes

DT-203NE			ALPHANUMERICAL LED. INDOORS			Ethernet	
DT-203/2SNE	Ethernet	20	30	2	1	615x170x120	Yes
DT-203/2DNE	Ethernet	20	30	2	2	615x170x120	Yes
DT-203/4SNE	Ethernet	20	30	4	1	615x317x120	Yes
DT-203/4DNE	Ethernet	20	30	4	1	615x317x120	Yes
DT-203/6SNE	Ethernet	20	30	6	1	615x464x120	Yes
DT-203/6DNE	Ethernet	20	30	6	1	615x464x120	Yes
DT-203/8SNE	Ethernet	20	30	8	1	615x611x120	Yes
DT-203/8DNE	Ethernet	20	30	8	1	615x611x120	Yes

DT-203NP			ALPHANUMERICAL LED. INDOORS			Profibus DP	
DT-203/2SNP	Profibus DP	20	30	2	1	615x170x120	Yes
DT-203/2DNP	Profibus DP	20	30	2	2	615x170x120	Yes
DT-203/4SNP	Profibus DP	20	30	4	1	615x317x120	Yes
DT-203/4DNP	Profibus DP	20	30	4	1	615x317x120	Yes
DT-203/6SNP	Profibus DP	20	30	6	1	615x464x120	Yes
DT-203/6DNP	Profibus DP	20	30	6	1	615x464x120	Yes
DT-203/8SNP	Profibus DP	20	30	8	1	615x611x120	Yes
DT-203/8DNP	Profibus DP	20	30	8	1	615x611x120	Yes

DT-203NW			ALPHANUMERICAL LED. INDOORS			Wifi	
DT-203/2SNW	Wifi	20	30	2	1	615x170x120	Yes
DT-203/2DNW	Wifi	20	30	2	2	615x170x120	Yes
DT-203/4SNW	Wifi	20	30	4	1	615x317x120	Yes
DT-203/4DNW	Wifi	20	30	4	1	615x317x120	Yes
DT-203/6SNW	Wifi	20	30	6	1	615x464x120	Yes
DT-203/6DNW	Wifi	20	30	6	1	615x464x120	Yes
DT-203/8SNW	Wifi	20	30	8	1	615x611x120	Yes
DT-203/8DNW	Wifi	20	30	8	1	615x611x120	Yes

S=1 Side

D= 2 Sides

OPTION RELATIVE HUMIDITY AND TEMPERATURE (+TH)

CABLES AND ACCESSORIES FOR DISPLAYS MULTILINE

SC-105C	Programming cable for DT-105, DT-110 and DT-203 displays
TDLwin	Software for programming alphanumeric displays
CONV485	Converter RS 232 / RS 485

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-105X ALPHANUMERICAL LED. INDOORS							RS-232/485
DT-105/1SX	Serial	20	50	1	1	985x118x120	Yes
DT-105/1DX	Serial	20	50	1	2	985x118x120	Yes
DT-105/2SX	Serial	20	50	2	1	985x224x120	Yes
DT-105/2DX	Serial	20	50	2	2	985x224x120	Yes
DT-105/3SX	Serial	20	50	3	1	985x330x120	Yes
DT-105/3DX	Serial	20	50	3	2	985x330x120	Yes
DT-105/4SX	Serial	20	50	4	1	985x436x120	Yes
DT-105/4DX	Serial	20	50	4	2	985x436x120	Yes
DT-105/5SX	Serial	20	50	5	1	985x542x120	Yes
DT-105/5DX	Serial	20	50	5	2	985x542x120	Yes
DT-105/6SX	Serial	20	50	6	1	985x648x120	Yes
DT-105/6DX	Serial	20	50	6	2	985x648x120	Yes
DT-105/7SX	Serial	20	50	7	1	985x754x120	Yes
DT-105/7DX	Serial	20	50	7	2	985x754x120	Yes
DT-105/8SX	Serial	20	50	8	1	985x860x120	Yes
DT-105/8DX	Serial	20	50	8	2	985x860x120	Yes

DT-105P ALPHANUMERICAL LED. INDOORS							BINARY
DT-105/1SP	Binary	20	50	1	1	985x118x120	Yes
DT-105/1DP	Binary	20	50	1	2	985x118x120	Yes
DT-105/2SP	Binary	20	50	2	1	985x224x120	Yes
DT-105/2DP	Binary	20	50	2	2	985x224x120	Yes
DT-105/3SP	Binary	20	50	3	1	985x330x120	Yes
DT-105/3DP	Binary	20	50	3	2	985x330x120	Yes
DT-105/4SP	Binary	20	50	4	1	985x436x120	Yes
DT-105/4DP	Binary	20	50	4	2	985x436x120	Yes
DT-105/5SP	Binary	20	50	5	1	985x542x120	Yes
DT-105/5DP	Binary	20	50	5	2	985x542x120	Yes
DT-105/6SP	Binary	20	50	6	1	985x648x120	Yes
DT-105/6DP	Binary	20	50	6	2	985x648x120	Yes

DT-105NE ALPHANUMERICAL LED. INDOORS							Ethernet
DT-105/1SNE	Ethernet	20	50	1	1	985x118x120	Yes
DT-105/1DNE	Ethernet	20	50	1	2	985x118x120	Yes
DT-105/2SNE	Ethernet	20	50	2	1	985x224x120	Yes
DT-105/2DNE	Ethernet	20	50	2	2	985x224x120	Yes
DT-105/3SNE	Ethernet	20	50	3	1	985x330x120	Yes
DT-105/3DNE	Ethernet	20	50	3	2	985x330x120	Yes
DT-105/4SNE	Ethernet	20	50	4	1	985x436x120	Yes
DT-105/4DNE	Ethernet	20	50	4	2	985x436x120	Yes
DT-105/5SNE	Ethernet	20	50	5	1	985x542x120	Yes
DT-105/5DNE	Ethernet	20	50	5	2	985x542x120	Yes
DT-105/6SNE	Ethernet	20	50	6	1	985x648x120	Yes
DT-105/6DNE	Ethernet	20	50	6	2	985x648x120	Yes
DT-105/7SNE	Ethernet	20	50	7	1	985x754x120	Yes
DT-105/7DNE	Ethernet	20	50	7	2	985x754x120	Yes
DT-105/8SNE	Ethernet	20	50	8	1	985x860x120	Yes
DT-105/8DNE	Ethernet	20	50	8	2	985x860x120	Yes

S=1 Side

D= 2 Sides

OPTION RELATIVE HUMIDITY AND TEMPERATURE (+TH)

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-105NP	ALPHANUMERICAL LED. INDOORS					Profibus DP	
DT-105/1SNP	Profibus DP	20	50	1	1	985x118x120	Yes
DT-105/1DNP	Profibus DP	20	50	1	2	985x118x120	Yes
DT-105/2SNP	Profibus DP	20	50	2	1	985x224x120	Yes
DT-105/2DNP	Profibus DP	20	50	2	2	985x224x120	Yes
DT-105/3SNP	Profibus DP	20	50	3	1	985x330x120	Yes
DT-105/3DNP	Profibus DP	20	50	3	2	985x330x120	Yes
DT-105/4SNP	Profibus DP	20	50	4	1	985x436x120	Yes
DT-105/4DNP	Profibus DP	20	50	4	2	985x436x120	Yes
DT-105/5SNP	Profibus DP	20	50	5	1	985x542x120	Yes
DT-105/5DNP	Profibus DP	20	50	5	2	985x542x120	Yes
DT-105/6SNP	Profibus DP	20	50	6	1	985x648x120	Yes
DT-105/6DNP	Profibus DP	20	50	6	2	985x648x120	Yes
DT-105/7SNP	Profibus DP	20	50	7	1	985x754x120	Yes
DT-105/7DNP	Profibus DP	20	50	7	2	985x754x120	Yes
DT-105/8SNP	Profibus DP	20	50	8	1	985x860x120	Yes
DT-105/8DNP	Profibus DP	20	50	8	2	985x860x120	Yes

DT-105NW	ALPHANUMERICAL LED. INDOORS					Wifi	
DT-105/1SNW	Wifi	20	50	1	1	985x118x120	Yes
DT-105/1DNW	Wifi	20	50	1	2	985x118x120	Yes
DT-105/2SNW	Wifi	20	50	2	1	985x224x120	Yes
DT-105/2DNW	Wifi	20	50	2	2	985x224x120	Yes
DT-105/3SNW	Wifi	20	50	3	1	985x330x120	Yes
DT-105/3DNW	Wifi	20	50	3	2	985x330x120	Yes
DT-105/4SNW	Wifi	20	50	4	1	985x436x120	Yes
DT-105/4DNW	Wifi	20	50	4	2	985x436x120	Yes
DT-105/5SNW	Wifi	20	50	5	1	985x542x120	Yes
DT-105/5DNW	Wifi	20	50	5	2	985x542x120	Yes
DT-105/6SNW	Wifi	20	50	6	1	985x648x120	Yes
DT-105/6DNW	Wifi	20	50	6	2	985x648x120	Yes
DT-105/7SNW	Wifi	20	50	7	1	985x754x120	Yes
DT-105/7DNW	Wifi	20	50	7	2	985x754x120	Yes
DT-105/8SNW	Wifi	20	50	8	1	985x860x120	Yes
DT-105/8DNW	Wifi	20	50	8	2	985x860x120	Yes

S=1 Side

D= 2 Sides

OPTION RELATIVE HUMIDITY AND TEMPERATURE (+TH)

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-106X ALPHANUMERICAL LED. OUTDOORS							RS-232/485
DT-106/1SX	Serial	20	50	1	1	985x118x120	Yes
DT-106/1DX	Serial	20	50	1	2	985x118x120	Yes
DT-106/2SX	Serial	20	50	2	1	985x224x120	Yes
DT-106/2DX	Serial	20	50	2	2	985x224x120	Yes
DT-106/3SX	Serial	20	50	3	1	985x330x120	Yes
DT-106/3DX	Serial	20	50	3	2	985x330x120	Yes
DT-106/4SX	Serial	20	50	4	1	985x436x120	Yes
DT-106/4DX	Serial	20	50	4	2	985x436x120	Yes
DT-106/5SX	Serial	20	50	5	1	985x542x120	Yes
DT-106/5DX	Serial	20	50	5	2	985x542x120	Yes
DT-106/6SX	Serial	20	50	6	1	985x648x120	Yes
DT-106/6DX	Serial	20	50	6	2	985x648x120	Yes
DT-106/7SX	Serial	20	50	7	1	985x754x120	Yes
DT-106/7DX	Serial	20	50	7	2	985x754x120	Yes
DT-106/8SX	Serial	20	50	8	1	985x860x120	Yes
DT-106/8DX	Serial	20	50	8	2	985x860x120	Yes

DT-106P ALPHANUMERICAL LED. OUTDOORS							BINARY
DT-106/1SP	Binary	20	50	1	1	985x118x120	Yes
DT-106/1DP	Binary	20	50	1	2	985x118x120	Yes
DT-106/2SP	Binary	20	50	2	1	985x224x120	Yes
DT-106/2DP	Binary	20	50	2	2	985x224x120	Yes
DT-106/3SP	Binary	20	50	3	1	985x330x120	Yes
DT-106/3DP	Binary	20	50	3	2	985x330x120	Yes
DT-106/4SP	Binary	20	50	4	1	985x436x120	Yes
DT-106/4DP	Binary	20	50	4	2	985x436x120	Yes
DT-106/5SP	Binary	20	50	5	1	985x542x120	Yes
DT-106/5DP	Binary	20	50	5	2	985x542x120	Yes
DT-106/6SP	Binary	20	50	6	1	985x648x120	Yes
DT-106/6DP	Binary	20	50	6	2	985x648x120	Yes

DT-106NE ALPHANUMERICAL LED. OUTDOORS							Ethernet
DT-106/1SNE	Ethernet	20	50	1	1	985x118x120	Yes
DT-106/1DNE	Ethernet	20	50	1	2	985x118x120	Yes
DT-106/2SNE	Ethernet	20	50	2	1	985x224x120	Yes
DT-106/2DNE	Ethernet	20	50	2	2	985x224x120	Yes
DT-106/3SNE	Ethernet	20	50	3	1	985x330x120	Yes
DT-106/3DNE	Ethernet	20	50	3	2	985x330x120	Yes
DT-106/4SNE	Ethernet	20	50	4	1	985x436x120	Yes
DT-106/4DNE	Ethernet	20	50	4	2	985x436x120	Yes
DT-106/5SNE	Ethernet	20	50	5	1	985x542x120	Yes
DT-106/5DNE	Ethernet	20	50	5	2	985x542x120	Yes
DT-106/6SNE	Ethernet	20	50	6	1	985x648x120	Yes
DT-106/6DNE	Ethernet	20	50	6	2	985x648x120	Yes
DT-106/7SNE	Ethernet	20	50	7	1	985x754x120	Yes
DT-106/7DNE	Ethernet	20	50	7	2	985x754x120	Yes
DT-106/8SNE	Ethernet	20	50	8	1	985x860x120	Yes
DT-106/8DNE	Ethernet	20	50	8	2	985x860x120	Yes

DT-106NP ALPHANUMERICAL LED. OUTDOORS							Profibus DP
DT-106/1SNP	Profibus DP	20	50	1	1	985x118x120	Yes
DT-106/1DNP	Profibus DP	20	50	1	2	985x118x120	Yes
DT-106/2SNP	Profibus DP	20	50	2	1	985x224x120	Yes
DT-106/2DNP	Profibus DP	20	50	2	2	985x224x120	Yes
DT-106/3SNP	Profibus DP	20	50	3	1	985x330x120	Yes
DT-106/3DNP	Profibus DP	20	50	3	2	985x330x120	Yes
DT-106/4SNP	Profibus DP	20	50	4	1	985x436x120	Yes
DT-106/4DNP	Profibus DP	20	50	4	2	985x436x120	Yes
DT-106/5SNP	Profibus DP	20	50	5	1	985x542x120	Yes
DT-106/5DNP	Profibus DP	20	50	5	2	985x542x120	Yes
DT-106/6SNP	Profibus DP	20	50	6	1	985x648x120	Yes
DT-106/6DNP	Profibus DP	20	50	6	2	985x648x120	Yes
DT-106/7SNP	Profibus DP	20	50	7	1	985x754x120	Yes
DT-106/7DNP	Profibus DP	20	50	7	2	985x754x120	Yes
DT-106/8SNP	Profibus DP	20	50	8	1	985x860x120	Yes
DT-106/8DNP	Profibus DP	20	50	8	2	985x860x120	Yes

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-106NW			ALPHANUMERICAL LED. OUTDOORS			Wifi	
DT-106/1SNW	Wifi	20	50	1	1	985x118x120	Yes
DT-106/1DNW	Wifi	20	50	1	2	985x118x120	Yes
DT-106/2SNW	Wifi	20	50	2	1	985x224x120	Yes
DT-106/2DNW	Wifi	20	50	2	2	985x224x120	Yes
DT-106/3SNW	Wifi	20	50	3	1	985x330x120	Yes
DT-106/3DNW	Wifi	20	50	3	2	985x330x120	Yes
DT-106/4SNW	Wifi	20	50	4	1	985x436x120	Yes
DT-106/4DNW	Wifi	20	50	4	2	985x436x120	Yes
DT-106/5SNW	Wifi	20	50	5	1	985x542x120	Yes
DT-106/5DNW	Wifi	20	50	5	2	985x542x120	Yes
DT-106/6SNW	Wifi	20	50	6	1	985x648x120	Yes
DT-106/6DNW	Wifi	20	50	6	2	985x648x120	Yes
DT-106/7SNW	Wifi	20	50	7	1	985x754x120	Yes
DT-106/7DNW	Wifi	20	50	7	2	985x754x120	Yes
DT-106/8SNW	Wifi	20	50	8	1	985x860x120	Yes
DT-106/8DNW	Wifi	20	50	8	2	985x860x120	Yes

DT-110X			ALPHANUMERICAL LED. INDOORS			RS-232/485	
DT-110/1SX	Serial	20	100	1	1	1886x165x120	Yes
DT-110/1DX	Serial	20	100	1	2	1886x165x120	Yes
DT-110/2SX	Serial	20	100	2	1	1886x378x120	Yes
DT-110/2DX	Serial	20	100	2	2	1886x378x120	Yes
DT-110/3SX	Serial	20	100	3	1	1886x591x120	Yes
DT-110/3DX	Serial	20	100	3	2	1886x591x120	Yes
DT-110/4SX	Serial	20	100	4	1	1886x805x120	Yes
DT-110/4DX	Serial	20	100	4	2	1886x805x120	Yes
DT-110/5SX	Serial	20	100	5	1	1886x1018x120	Yes
DT-110/5DX	Serial	20	100	5	2	1886x1018x120	Yes
DT-110/6SX	Serial	20	100	6	1	1886x1232x120	Yes
DT-110/6DX	Serial	20	100	6	2	1886x1232x120	Yes
DT-110/7SX	Serial	20	100	7	1	1886x1445x120	Yes
DT-110/7DX	Serial	20	100	7	2	1886x1445x120	Yes
DT-110/8SX	Serial	20	100	8	1	1886x1659x120	Yes
DT-110/8DX	Serial	20	100	8	2	1886x1659x120	Yes

DT-110P			ALPHANUMERICAL LED. INDOORS			BINARY	
DT-110/1SP	Binary	20	100	1	1	1886x165x120	Yes
DT-110/1DP	Binary	20	100	1	2	1886x165x120	Yes
DT-110/2SP	Binary	20	100	2	1	1886x378x120	Yes
DT-110/2DP	Binary	20	100	2	2	1886x378x120	Yes
DT-110/3SP	Binary	20	100	3	1	1886x591x120	Yes
DT-110/3DP	Binary	20	100	3	2	1886x591x120	Yes
DT-110/4SP	Binary	20	100	4	1	1886x805x120	Yes
DT-110/4DP	Binary	20	100	4	2	1886x805x120	Yes
DT-110/5SP	Binary	20	100	5	1	1886x1018x120	Yes
DT-110/5DP	Binary	20	100	5	2	1886x1018x120	Yes
DT-110/6SP	Binary	20	100	6	1	1886x1232x120	Yes
DT-110/6DP	Binary	20	100	6	2	1886x1232x120	Yes

S=1 Side

D= 2 Sides

OPTION RELATIVE HUMIDITY AND TEMPERATURE (+TH)

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-110NE	ALPHANUMERICAL LED. INDOORS					Ethernet	
DT-110/1SNE	Serial	20	100	1	1	1886x165x120	Yes
DT-110/1DNE	Serial	20	100	1	2	1886x165x120	Yes
DT-110/2SNE	Serial	20	100	2	1	1886x378x120	Yes
DT-110/2DNE	Serial	20	100	2	2	1886x378x120	Yes
DT-110/3SNE	Serial	20	100	3	1	1886x591x120	Yes
DT-110/3DNE	Serial	20	100	3	2	1886x591x120	Yes
DT-110/4SNE	Serial	20	100	4	1	1886x805x120	Yes
DT-110/4DNE	Serial	20	100	4	2	1886x805x120	Yes
DT-110/5SNE	Serial	20	100	5	1	1886x1018x120	Yes
DT-110/5DNE	Serial	20	100	5	2	1886x1018x120	Yes
DT-110/6SNE	Serial	20	100	6	1	1886x1232x120	Yes
DT-110/6DNE	Serial	20	100	6	2	1886x1232x120	Yes
DT-110/7SNE	Serial	20	100	7	1	1886x1445x120	Yes
DT-110/7DNE	Serial	20	100	7	2	1886x1445x120	Yes
DT-110/8SNE	Serial	20	100	8	1	1886x1659x120	Yes
DT-110/8DNE	Serial	20	100	8	2	1886x1659x120	Yes

DT-110NP	ALPHANUMERICAL LED. INDOORS					Profibus DP	
DT-110/1SNP	Profibus DP	20	100	1	1	1886x165x120	Yes
DT-110/1DNP	Profibus DP	20	100	1	2	1886x165x120	Yes
DT-110/2SNP	Profibus DP	20	100	2	1	1886x378x120	Yes
DT-110/2DNP	Profibus DP	20	100	2	2	1886x378x120	Yes
DT-110/3SNP	Profibus DP	20	100	3	1	1886x591x120	Yes
DT-110/3DNP	Profibus DP	20	100	3	2	1886x591x120	Yes
DT-110/4SNP	Profibus DP	20	100	4	1	1886x805x120	Yes
DT-110/4DNP	Profibus DP	20	100	4	2	1886x805x120	Yes
DT-110/5SNP	Profibus DP	20	100	5	1	1886x1018x120	Yes
DT-110/5DNP	Profibus DP	20	100	5	2	1886x1018x120	Yes
DT-110/6SNP	Profibus DP	20	100	6	1	1886x1232x120	Yes
DT-110/6DNP	Profibus DP	20	100	6	2	1886x1232x120	Yes
DT-110/7SNP	Profibus DP	20	100	7	1	1886x1445x120	Yes
DT-110/7DNP	Profibus DP	20	100	7	2	1886x1445x120	Yes
DT-110/8SNP	Profibus DP	20	100	8	1	1886x1659x120	Yes
DT-110/8DNP	Profibus DP	20	100	8	2	1886x1659x120	Yes

DT-110NW	ALPHANUMERICAL LED. INDOORS					Wifi	
DT-110/1SNW	Wifi	20	100	1	1	1886x165x120	Yes
DT-110/1DNW	Wifi	20	100	1	2	1886x165x120	Yes
DT-110/2SNW	Wifi	20	100	2	1	1886x378x120	Yes
DT-110/2DNW	Wifi	20	100	2	2	1886x378x120	Yes
DT-110/3SNW	Wifi	20	100	3	1	1886x591x120	Yes
DT-110/3DNW	Wifi	20	100	3	2	1886x591x120	Yes
DT-110/4SNW	Wifi	20	100	4	1	1886x805x120	Yes
DT-110/4DNW	Wifi	20	100	4	2	1886x805x120	Yes
DT-110/5SNW	Wifi	20	100	5	1	1886x1018x120	Yes
DT-110/5DNW	Wifi	20	100	5	2	1886x1018x120	Yes
DT-110/6SNW	Wifi	20	100	6	1	1886x1232x120	Yes
DT-110/6DNW	Wifi	20	100	6	2	1886x1232x120	Yes
DT-110/7SNW	Wifi	20	100	7	1	1886x1445x120	Yes
DT-110/7DNW	Wifi	20	100	7	2	1886x1445x120	Yes
DT-110/8SNW	Wifi	20	100	8	1	1886x1659x120	Yes
DT-110/8DNW	Wifi	20	100	8	2	1886x1659x120	Yes

S=1 Side

D= 2 Sides

OPTION RELATIVE HUMIDITY AND TEMPERATURE (+TH)

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-111X	ALPHANUMERICAL LED. OUTDOORS					RS-232/485	
DT-111/1SX	Serial	20	100	1	1	1886x165x120	Yes
DT-111/1DX	Serial	20	100	1	2	1886x165x120	Yes
DT-111/2SX	Serial	20	100	2	1	1886x378x120	Yes
DT-111/2DX	Serial	20	100	2	2	1886x378x120	Yes
DT-111/3SX	Serial	20	100	3	1	1886x591x120	Yes
DT-111/3DX	Serial	20	100	3	2	1886x591x120	Yes
DT-111/4SX	Serial	20	100	4	1	1886x805x120	Yes
DT-111/4DX	Serial	20	100	4	2	1886x805x120	Yes
DT-111/5SX	Serial	20	100	5	1	1886x1018x120	Yes
DT-111/5DX	Serial	20	100	5	2	1886x1018x120	Yes
DT-111/6SX	Serial	20	100	6	1	1886x1232x120	Yes
DT-111/6DX	Serial	20	100	6	2	1886x1232x120	Yes
DT-111/7SX	Serial	20	100	7	1	1886x1445x120	Yes
DT-111/7DX	Serial	20	100	7	2	1886x1445x120	Yes
DT-111/8SX	Serial	20	100	8	1	1886x1659x120	Yes
DT-111/8DX	Serial	20	100	8	1	1886x1659x120	Yes

DT-111P	ALPHANUMERICAL LED. OUTDOORS					BINARY	
DT-111/1SP	Binary	20	100	1	1	1886x165x120	Yes
DT-111/1DP	Binary	20	100	1	2	1886x165x120	Yes
DT-111/2SP	Binary	20	100	2	1	1886x378x120	Yes
DT-111/2DP	Binary	20	100	2	2	1886x378x120	Yes
DT-111/3SP	Binary	20	100	3	1	1886x591x120	Yes
DT-111/3DP	Binary	20	100	3	2	1886x591x120	Yes
DT-111/4SP	Binary	20	100	4	1	1886x805x120	Yes
DT-111/4DP	Binary	20	100	4	2	1886x805x120	Yes
DT-111/5SP	Binary	20	100	5	1	1886x1018x120	Yes
DT-111/5DP	Binary	20	100	5	2	1886x1018x120	Yes
DT-111/6SP	Binary	20	100	6	1	1886x1232x120	Yes
DT-111/6DP	Binary	20	100	6	2	1886x1232x120	Yes

DT-111NE	ALPHANUMERICAL LED. OUTDOORS					Ethernet	
DT-111/1SNE	Serial	20	100	1	1	1886x165x120	Yes
DT-111/1DNE	Serial	20	100	1	2	1886x165x120	Yes
DT-111/2SNE	Serial	20	100	2	1	1886x378x120	Yes
DT-111/2DNE	Serial	20	100	2	2	1886x378x120	Yes
DT-111/3SNE	Serial	20	100	3	1	1886x591x120	Yes
DT-111/3DNE	Serial	20	100	3	2	1886x591x120	Yes
DT-111/4SNE	Serial	20	100	4	1	1886x805x120	Yes
DT-111/4DNE	Serial	20	100	4	2	1886x805x120	Yes
DT-111/5SNE	Serial	20	100	5	1	1886x1018x120	Yes
DT-111/5DNE	Serial	20	100	5	2	1886x1018x120	Yes
DT-111/6SNE	Serial	20	100	6	1	1886x1232x120	Yes
DT-111/6DNE	Serial	20	100	6	2	1886x1232x120	Yes
DT-111/7SNE	Serial	20	100	7	1	1886x1445x120	Yes
DT-111/7DNE	Serial	20	100	7	2	1886x1445x120	Yes
DT-111/8SNE	Serial	20	100	8	1	1886x1659x120	Yes
DT-111/8DNE	Serial	20	100	8	2	1886x1659x120	Yes

DT-111NP	ALPHANUMERICAL LED. OUTDOORS					Profibus DP	
DT-111/1SNP	Profibus DP	20	100	1	1	1886x165x120	Yes
DT-111/1DNP	Profibus DP	20	100	1	2	1886x165x120	Yes
DT-111/2SNP	Profibus DP	20	100	2	1	1886x378x120	Yes
DT-111/2DNP	Profibus DP	20	100	2	2	1886x378x120	Yes
DT-111/3SNP	Profibus DP	20	100	3	1	1886x591x120	Yes
DT-111/3DNP	Profibus DP	20	100	3	2	1886x591x120	Yes
DT-111/4SNP	Profibus DP	20	100	4	1	1886x805x120	Yes
DT-111/4DNP	Profibus DP	20	100	4	2	1886x805x120	Yes
DT-111/5SNP	Profibus DP	20	100	5	1	1886x1018x120	Yes
DT-111/5DNP	Profibus DP	20	100	5	2	1886x1018x120	Yes
DT-111/6SNP	Profibus DP	20	100	6	1	1886x1232x120	Yes
DT-111/6DNP	Profibus DP	20	100	6	2	1886x1232x120	Yes
DT-111/7SNP	Profibus DP	20	100	7	1	1886x1445x120	Yes
DT-111/7DNP	Profibus DP	20	100	7	2	1886x1445x120	Yes
DT-111/8SNP	Profibus DP	20	100	8	1	1886x1659x120	Yes
DT-111/8DNP	Profibus DP	20	100	8	2	1886x1659x120	Yes

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-111NW	ALPHANUMERICAL LED. OUTDOORS					Wifi	
DT-111/1SNW	Wifi	20	100	1	1	1886x165x120	Yes
DT-111/1DNW	Wifi	20	100	1	2	1886x165x120	Yes
DT-111/2SNW	Wifi	20	100	2	1	1886x378x120	Yes
DT-111/2DNW	Wifi	20	100	2	2	1886x378x120	Yes
DT-111/3SNW	Wifi	20	100	3	1	1886x591x120	Yes
DT-111/3DNW	Wifi	20	100	3	2	1886x591x120	Yes
DT-111/4SNW	Wifi	20	100	4	1	1886x805x120	Yes
DT-111/4DNW	Wifi	20	100	4	2	1886x805x120	Yes
DT-111/5SNW	Wifi	20	100	5	1	1886x1018x120	Yes
DT-111/5DNW	Wifi	20	100	5	2	1886x1018x120	Yes
DT-111/6SNW	Wifi	20	100	6	1	1886x1232x120	Yes
DT-111/6DNW	Wifi	20	100	6	2	1886x1232x120	Yes
DT-111/7SNW	Wifi	20	100	7	1	1886x1445x120	Yes
DT-111/7DNW	Wifi	20	100	7	2	1886x1445x120	Yes
DT-111/8SNW	Wifi	20	100	8	1	1886x1659x120	Yes
DT-111/8DNW	Wifi	20	100	8	2	1886x1659x120	Yes

S=1 Side

D= 2 Sides

OPTION RELATIVE HUMIDITY AND TEMPERATURE (+TH)

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-203eX	ALPHANUMERICAL LED. IP65					RS-232/485	
DT-203e/2SX	Serial	20	30	2	1	615x170x120	Yes
DT-203e/2DX	Serial	20	30	2	2	615x170x120	Yes
DT-203eP	ALPHANUMERICAL LED. IP65					BINARY	
DT-203e/2SP	Binary	20	30	2	1	615x170x120	Yes
DT-203e/2DP	Binary	20	30	2	2	615x170x120	Yes
DT-203eNE	ALPHANUMERICAL LED. IP65					Ethernet	
DT-203e/2SNE	Ethernet	20	30	2	1	615x170x120	Yes
DT-203e/2DNE	Ethernet	20	30	2	2	615x170x120	Yes
DT-203eNP	ALPHANUMERICAL LED. IP65					Profibus	
DT-203e/2SNP	Profibus DP	20	30	2	1	615x170x120	Yes
DT-203e/2DNP	Profibus DP	20	30	2	2	615x170x120	Yes
DT-203eNW	ALPHANUMERICAL LED. IP65					Wifi	
DT-203e/2SNW	Wifi	20	30	2	1	615x170x120	Yes
DT-203e/2DNW	Wifi	20	30	2	2	615x170x120	Yes
DT-105eX	ALPHANUMERICAL LED. IP65					RS-232/485	
DT-105e/1SX	Serial	20	50	1	1	985x118x120	Yes
DT-105e/1DX	Serial	20	50	1	2	985x118x120	Yes
DT-105eP	ALPHANUMERICAL LED. IP65					BINARY	
DT-105e/1SP	Binary	20	50	1	1	985x118x120	Yes
DT-105e/1DP	Binary	20	50	1	2	985x118x120	Yes
DT-105eNE	ALPHANUMERICAL LED. IP65					Ethernet	
DT-105e/1SNE	Ethernet	20	50	1	1	985x118x120	Yes
DT-105e/1DNE	Ethernet	20	50	1	2	985x118x120	Yes
DT-105eNP	ALPHANUMERICAL LED. IP65					Profibus	
DT-105e/1SNP	Profibus DP	20	50	1	1	985x130x120	Yes
DT-105e/1DNP	Profibus DP	20	50	1	2	985x130x120	Yes
DT-105eNW	ALPHANUMERICAL LED. IP65					Wifi	
DT-105e/1SNW	Wifi	20	50	1	1	985x118x120	Yes
DT-105e/1DNW	Wifi	20	50	1	2	985x118x120	Yes
DT-110eX	ALPHANUMERICAL LED. IP65					RS-232/485	
DT-110e/1SX	Serial	20	100	1	1	1886x165x120	Yes
DT-110e/1DX	Serial	20	100	1	2	1886x165x120	Yes
DT-110eP	ALPHANUMERICAL LED. IP65					BINARY	
DT-110e/1SP	Binary	20	100	1	1	1886x165x120	Yes
DT-110e/1DP	Binary	20	100	1	2	1886x165x120	Yes
DT-110eNE	ALPHANUMERICAL LED. IP65					Ethernet	
DT-110e/1SNE	Serial	20	100	1	1	1886x165x120	Yes
DT-110e/1DNE	Serial	20	100	1	2	1886x165x120	Yes
DT-110eNP	ALPHANUMERICAL LED. IP65					Profibus	
DT-110e/1SNP	Profibus DP	20	100	1	1	1886x165x120	Yes
DT-110e/1DNP	Profibus DP	20	100	1	2	1886x165x120	Yes
DT-110eNW	ALPHANUMERICAL LED. IP65					Wifi	
DT-110e/1SNW	Wifi	20	100	1	1	1886x165x120	Yes
DT-110e/1DNW	Wifi	20	100	1	2	1886x165x120	Yes

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DT-106eX	ALPHANUMERICAL LED. IP65					RS-232/485	
DT-106e/1SX	Serial	20	50	1	1	985x118x120	Yes
DT-106e/1DX	Serial	20	50	1	2	985x118x120	Yes

DT-106eP	ALPHANUMERICAL LED. IP65					BINARY	
DT-106e/1SP	Binary	20	50	1	1	985x118x120	Yes
DT-106e/1DP	Binary	20	50	1	2	985x118x120	Yes

DT-106eNE	ALPHANUMERICAL LED. IP65					Ethernet	
DT-106e/1SNE	Ethernet	20	50	1	1	985x118x120	Yes
DT-106e/1DNE	Ethernet	20	50	1	2	985x118x120	Yes

DT-106eNP	ALPHANUMERICAL LED. IP65					Profibus	
DT-106e/1SNP	Profibus DP	20	50	1	1	985x130x120	Yes
DT-106e/1DNP	Profibus DP	20	50	1	2	985x130x120	Yes

DT-106eNW	ALPHANUMERICAL LED. IP65					Wifi	
DT-106e/1SNW	Wifi	20	50	1	1	985x118x120	Yes
DT-106e/1DNW	Wifi	20	50	1	2	985x118x120	Yes

DT-111eX	ALPHANUMERICAL LED. IP65					RS-232/485	
DT-111e/1SX	Serial	20	100	1	1	1886x165x120	Yes
DT-111e/1DX	Serial	20	100	1	2	1886x165x120	Yes

DT-111eP	ALPHANUMERICAL LED. IP65					BINARY	
DT-111e/1SP	Binary	20	100	1	1	1886x165x120	Yes
DT-111e/1DP	Binary	20	100	1	2	1886x165x120	Yes

DT-111eNE	ALPHANUMERICAL LED. IP65					Ethernet	
DT-111e/1SNE	Serial	20	100	1	1	1886x165x120	Yes
DT-111e/1DNE	Serial	20	100	1	2	1886x165x120	Yes

DT-111eNP	ALPHANUMERICAL LED. IP65					Profibus	
DT-111e/1SNP	Profibus DP	20	100	1	1	1886x165x120	Yes
DT-111e/1DNP	Profibus DP	20	100	1	2	1886x165x120	Yes

DT-111eNW	ALPHANUMERICAL LED. IP65					Wifi	
DT-111e/1SNW	Wifi	20	100	1	1	1886x165x120	Yes
DT-111e/1DNW	Wifi	20	100	1	2	1886x165x120	Yes

S=1 Side

D= 2 Sides

OPTION RELATIVE HUMIDITY AND TEMPERATURE IP65. (+TH)

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DN-107 Cube, BCD inputs . 57mm of Digit							
DN-107/2B-150	Binary	2	57	1	4	140x140x140	-
DN-107/2B-400	Binary	2	57	1	4	140x140x140	-
DN-107/3B-150	Binary	3	57	1	4	191x191x146	-
DN-107/3B-400	Binary	3	57	1	4	191x191x146	-
DN-107/3B-600	Binary	3	57	1	4	191x191x146	-

DN-108 BCD. 20mm. of Digit							
DN-108	Binary	2	20	1	1	72x36x127	-

DN-109X Digit of 57mm. Repeater RS-232/RS485. INDOOR USE.							
DN-109/3SX	Serial	3	57	1	1	210x122x120	-
DN-109/4SX	Serial	4	57	1	1	288x122x120	-
DN-109/4DX	Serial	4	57	1	2	288x122x120	-
DN-109/5SX	Serial	5	57	1	1	288x122x120	-
DN-109/5DX	Serial	5	57	1	2	288x122x120	-
DN-109/6SX	Serial	6	57	1	1	336x122x120	-
DN-109/6DX	Serial	6	57	1	2	336x122x120	-
DN-109/7SX	Serial	7	57	1	1	382x122x120	-
DN-109/7DX	Serial	7	57	1	2	382x122x120	-
DN-109/8SX	Serial	8	57	1	1	430x122x120	-
DN-109/8DX	Serial	8	57	1	2	430x122x120	-
DN-109/9SX	Serial	9	57	1	1	478x122x120	-
DN-109/9DX	Serial	9	57	1	2	478x122x120	-
DN-109/10SX	Serial	10	57	1	1	526x122x120	-
DN-109/10DX	Serial	10	57	1	2	526x122x120	-

DN-109C/X 57mm COLOR Repeater RS-232/RS485. INDOOR USE.							
DN-109C/3SX	Serial	3	57	1	1	210x122x120	-
DN-109C/4SX	Serial	4	57	1	1	288x122x120	-
DN-109C/4DX	Serial	4	57	1	2	288x122x120	-
DN-109C/5SX	Serial	5	57	1	1	288x122x120	-
DN-109C/5DX	Serial	5	57	1	2	288x122x120	-
DN-109C/6SX	Serial	6	57	1	1	336x122x120	-
DN-109C/6DX	Serial	6	57	1	2	336x122x120	-
DN-109C/7SX	Serial	7	57	1	1	382x122x120	-
DN-109C/7DX	Serial	7	57	1	2	382x122x120	-
DN-109C/8SX	Serial	8	57	1	1	430x122x120	-
DN-109C/8DX	Serial	8	57	1	2	430x122x120	-
DN-109C/9SX	Serial	9	57	1	1	478x122x120	-
DN-109C/9DX	Serial	9	57	1	2	478x122x120	-
DN-109C/10SX	Serial	10	57	1	1	526x122x120	-
DN-109C/10DX	Serial	10	57	1	2	526x122x120	-

DN-109P Digit of 57mm. Control Binary. INDOOR USE							
DN-109/3SP	Binary	3	57	1	1	210x122x120	-
DN-109/4SP	Binary	4	57	1	1	288x122x120	-
DN-109/4DP	Binary	4	57	1	2	288x122x120	-
DN-109/5SP	Binary	5	57	1	1	288x122x120	-
DN-109/5DP	Binary	5	57	1	2	288x122x120	-
DN-109/6SP	Binary	6	57	1	1	336x122x120	-
DN-109/6DP	Binary	6	57	1	2	336x122x120	-
DN-109/7SP	Binary	7	57	1	1	382x122x120	-
DN-109/7DP	Binary	7	57	1	2	382x122x120	-
DN-109/8SP	Binary	8	57	1	1	430x122x120	-
DN-109/8DP	Binary	8	57	1	2	430x122x120	-
DN-109/9SP	Binary	9	57	1	1	478x122x120	-
DN-109/9DP	Binary	9	57	1	2	478x122x120	-
DN-109/10SP	Binary	10	57	1	1	526x122x120	-
DN-109/10DP	Binary	10	57	1	2	526x122x120	-

DN-109TH Digit of 57mm. Temperature and humidity. INDOOR USE							
DN-109/STH	Temp. and humid	5	57	1	1	288x122x120	-
DN-109/DTH	Temp. and humid	5	57	1	2	288x122x120	-

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr.	From PC
OPTION: POWER SUPPLY 24Vcc								
Probe TH 2m								

S=1 Side

D= 2 Sides

Opti. relays (PR)	To add							
Option Serial L.(PX)	To add							
Option Text leds	Models S	+TL				+96mm		
Option Text vinyl	Models S	+TV				+96mm		
Option Text leds	Models D	+TL				+96mm		
Option Text vinyl	Models D	+TV				+96mm		
Models PR =	Models P + Option relays							
Models PX =	Models P + Option serial line							
Models PXR =	Models P + Option serial line + Option relays							

DN-109NE	Digit of 57mm.	Ethernet. INDOOR					
DN-109/3SNE	Ethernet	3	57	1	1	210x122x120	-
DN-109/4SNE	Ethernet	4	57	1	1	288x122x120	-
DN-109/4DNE	Ethernet	4	57	1	2	288x122x120	-
DN-109/5SNE	Ethernet	5	57	1	1	288x122x120	-
DN-109/5DNE	Ethernet	5	57	1	2	288x122x120	-
DN-109/6SNE	Ethernet	6	57	1	1	336x122x120	-
DN-109/6DNE	Ethernet	6	57	1	2	336x122x120	-
DN-109/7SNE	Ethernet	7	57	1	1	382x122x120	-
DN-109/7DNE	Ethernet	7	57	1	2	382x122x120	-
DN-109/8SNE	Ethernet	8	57	1	1	430x122x120	-
DN-109/8DNE	Ethernet	8	57	1	2	430x122x120	-
DN-109/9SNE	Ethernet	9	57	1	1	478x122x120	-
DN-109/9DNE	Ethernet	9	57	1	2	478x122x120	-
DN-109/10SNE	Ethernet	10	57	1	1	526x122x120	-
DN-109/10DNE	Ethernet	10	57	1	2	526x122x120	-

DN-109NP	Digit of 57mm.	Profibus-DP. INDOOR					
DN-109/3SNP	Profibus-DP	3	57	1	1	210x122x120	-
DN-109/4SNP	Profibus-DP	4	57	1	1	288x122x120	-
DN-109/4DNP	Profibus-DP	4	57	1	2	288x122x120	-
DN-109/5SNP	Profibus-DP	5	57	1	1	288x122x120	-
DN-109/5DNP	Profibus-DP	5	57	1	2	288x122x120	-
DN-109/6SNP	Profibus-DP	6	57	1	1	336x122x120	-
DN-109/6DNP	Profibus-DP	6	57	1	2	336x122x120	-
DN-109/7SNP	Profibus-DP	7	57	1	1	382x122x120	-
DN-109/7DNP	Profibus-DP	7	57	1	2	382x122x120	-
DN-109/8SNP	Profibus-DP	8	57	1	1	430x122x120	-
DN-109/8DNP	Profibus-DP	8	57	1	2	430x122x120	-
DN-109/9SNP	Profibus-DP	9	57	1	1	478x122x120	-
DN-109/9DNP	Profibus-DP	9	57	1	2	478x122x120	-
DN-109/10SNP	Profibus-DP	10	57	1	1	526x122x120	-
DN-109/10DNP	Profibus-DP	10	57	1	2	526x122x120	-

DN-109NW	Digit of 57mm.	Wifi. INDOOR					
DN-109/3SNW	Wifi	3	57	1	1	210x122x120	-
DN-109/4SNW	Wifi	4	57	1	1	288x122x120	-
DN-109/4DNW	Wifi	4	57	1	2	288x122x120	-
DN-109/5SNW	Wifi	5	57	1	1	288x122x120	-
DN-109/5DNW	Wifi	5	57	1	2	288x122x120	-
DN-109/6SNW	Wifi	6	57	1	1	336x122x120	-
DN-109/6DNW	Wifi	6	57	1	2	336x122x120	-
DN-109/7SNW	Wifi	7	57	1	1	382x122x120	-
DN-109/7DNW	Wifi	7	57	1	2	382x122x120	-
DN-109/8SNW	Wifi	8	57	1	1	430x122x120	-
DN-109/8DNW	Wifi	8	57	1	2	430x122x120	-
DN-109/9SNW	Wifi	9	57	1	1	478x122x120	-
DN-109/9DNW	Wifi	9	57	1	2	478x122x120	-
DN-109/10SNW	Wifi	10	57	1	1	526x122x120	-
DN-109/10DNW	Wifi	10	57	1	2	526x122x120	-

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DN-109AP	Digit of 57mm.		Analog input. INDOOR				
DN-109/3SAP	Process	3	57	1	1	210x122x120	-
DN-109/3DAP	Process	3	57	1	2	288x122x120	-
DN-109/4SAP	Process	4	57	1	1	288x122x120	-
DN-109/4DAP	Process	4	57	1	2	288x122x120	-
DN-109/5SAP	Process	5	57	1	1	288x122x120	-
DN-109/5DAP	Process	5	57	1	2	288x122x120	-

DN-109AT	Digit of 57mm.		Analog input. INDOOR				
DN-109/3SAT	Temperature	3	57	1	1	210x122x120	-
DN-109/3DAT	Temperature	3	57	1	2	288x122x120	-
DN-109/4SAT	Temperature	4	57	1	1	288x122x120	-
DN-109/4DAT	Temperature	4	57	1	2	288x122x120	-
DN-109/5SAT	Temperature	5	57	1	1	288x122x120	-
DN-109/5DAT	Temperature	5	57	1	2	288x122x120	-

DN-109C/AP	57mm COLOR		Analog input. INDOOR				
DN-109C/3SAP	Process	3	57	1	1	210x122x120	-
DN-109C/3DAP	Process	3	57	1	2	288x122x120	-
DN-109C/4SAP	Process	4	57	1	1	288x122x120	-
DN-109C/4DAP	Process	4	57	1	2	288x122x120	-
DN-109C/5SAP	Process	5	57	1	1	288x122x120	-
DN-109C/5DAP	Process	5	57	1	2	288x122x120	-

DN-109C/AT	57mm COLOR		Analog input. INDOOR				
DN-109C/3SAT	Temperature	3	57	1	1	210x122x120	-
DN-109C/3DAT	Temperature	3	57	1	2	288x122x120	-
DN-109C/4SAT	Temperature	4	57	1	1	288x122x120	-
DN-109C/4DAT	Temperature	4	57	1	2	288x122x120	-
DN-109C/5SAT	Temperature	5	57	1	1	288x122x120	-
DN-109/C5DAT	Temperature	5	57	1	2	288x122x120	-

OPTION: POWER SUPPLY 24Vcc

S=1 Side

D= 2 Sides

DN-109 / <u> </u> APX	Serial line						To add
DN-109 / <u> </u> ATX	Serial line						To add
DN-109 / <u> </u> APR	Output relays						To add
DN-109 / <u> </u> ATR	Output relays						To add
DN-109 / <u> </u> APXR	Serial line + relays						To add
DN-109 / <u> </u> ATXR	Serial line + relays						To add

Option Text leds	Models S	+TL			1	+96mm	To add
Option Text vinyl	Models S	+TV			2	+96mm	To add
Option Text leds	Models D	+TL			1	+96mm	To add
Option Text vinyl	Models D	+TV			2	+96mm	To add

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr.	From PC
DN-109eX	Digit of 57mm.						Repeater RS-232/RS485. IP65.	
DN-109e/3SX	Serial	3	57	1	1	210x122x120	-	-
DN-109e/4SX	Serial	4	57	1	1	288x122x120	-	-
DN-109e/4DX	Serial	4	57	1	2	288x122x120	-	-
DN-109e/5SX	Serial	5	57	1	1	288x122x120	-	-
DN-109e/5DX	Serial	5	57	1	2	288x122x120	-	-
DN-109e/6SX	Serial	6	57	1	1	336x122x120	-	-
DN-109e/6DX	Serial	6	57	1	2	336x122x120	-	-
DN-109e/7SX	Serial	7	57	1	1	382x122x120	-	-
DN-109e/7DX	Serial	7	57	1	2	382x122x120	-	-
DN-109e/8SX	Serial	8	57	1	1	430x122x120	-	-
DN-109e/8DX	Serial	8	57	1	2	430x122x120	-	-
DN-109e/9SX	Serial	9	57	1	1	478x122x120	-	-
DN-109e/9DX	Serial	9	57	1	2	478x122x120	-	-
DN-109e/10SX	Serial	10	57	1	1	526x122x120	-	-
DN-109e/10DX	Serial	10	57	1	2	526x122x120	-	-

DN-109CeX	57mm COLOR						Repeater RS-232/RS485. IP65.	
DN-109Ce/3SX	Serial	3	57	1	1	210x122x120	-	-
DN-109Ce/4SX	Serial	4	57	1	1	288x122x120	-	-
DN-109Ce/4DX	Serial	4	57	1	2	288x122x120	-	-
DN-109Ce/5SX	Serial	5	57	1	1	288x122x120	-	-
DN-109Ce/5DX	Serial	5	57	1	2	288x122x120	-	-
DN-109Ce/6SX	Serial	6	57	1	1	336x122x120	-	-
DN-109Ce/6DX	Serial	6	57	1	2	336x122x120	-	-
DN-109Ce/7SX	Serial	7	57	1	1	382x122x120	-	-
DN-109Ce/7DX	Serial	7	57	1	2	382x122x120	-	-
DN-109Ce/8SX	Serial	8	57	1	1	430x122x120	-	-
DN-109Ce/8DX	Serial	8	57	1	2	430x122x120	-	-
DN-109Ce/9SX	Serial	9	57	1	1	478x122x120	-	-
DN-109Ce/9DX	Serial	9	57	1	2	478x122x120	-	-
DN-109Ce/10SX	Serial	10	57	1	1	526x122x120	-	-
DN-109Ce/10DX	Serial	10	57	1	2	526x122x120	-	-

DN-109eP	Digit of 57mm.						Control Binary. IP65	
DN-109e/3SP	Binary	3	57	1	1	210x122x120	-	-
DN-109e/4SP	Binary	4	57	1	1	288x122x120	-	-
DN-109e/4DP	Binary	4	57	1	2	288x122x120	-	-
DN-109e/5SP	Binary	5	57	1	1	288x122x120	-	-
DN-109e/5DP	Binary	5	57	1	2	288x122x120	-	-
DN-109e/6SP	Binary	6	57	1	1	336x122x120	-	-
DN-109e/6DP	Binary	6	57	1	2	336x122x120	-	-
DN-109e/7SP	Binary	7	57	1	1	382x122x120	-	-
DN-109e/7DP	Binary	7	57	1	2	382x122x120	-	-
DN-109e/8SP	Binary	8	57	1	1	430x122x120	-	-
DN-109e/8DP	Binary	8	57	1	2	430x122x120	-	-
DN-109e/9SP	Binary	9	57	1	1	478x122x120	-	-
DN-109e/9DP	Binary	9	57	1	2	478x122x120	-	-
DN-109e/10SP	Binary	10	57	1	1	526x122x120	-	-
DN-109e/10DP	Binary	10	57	1	2	526x122x120	-	-

DN-109eTH	Digit of 57mm.						Temperature and humidity. IP65	
DN-109e/STH	Temp. and humid	5	57	1	1	288x122x120	-	-
DN-109e/DTH	Temp. and humid	5	57	1	2	288x122x120	-	-

OPTION: POWER SUPPLY 24Vcc

Probe TH 2m

S=1 Side

D= 2 Sides

Opti. relays (PR)	To add							
Option Serial L.(PX)	To add							
Option Text leds	Models S	+TL				+96mm		
Option Text vinyl	Models S	+TV				+96mm		
Option Text leds	Models D	+TL				+96mm		
Option Text vinyl	Models D	+TV				+96mm		
Models PR =	Models P + Option relays							
Models PX =	Models P + Option serial line							
Models PXR =	Models P + Option serial line + Option relays							

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DN-109eNE		Digit of 57mm.		Ethernet IP65			
DN-109e/3SNE	Ethernet	3	57	1	1	210x122x120	-
DN-109e/4SNE	Ethernet	4	57	1	1	288x122x120	-
DN-109e/4DNE	Ethernet	4	57	1	2	288x122x120	-
DN-109e/5SNE	Ethernet	5	57	1	1	288x122x120	-
DN-109e/5DNE	Ethernet	5	57	1	2	288x122x120	-
DN-109e/6SNE	Ethernet	6	57	1	1	336x122x120	-
DN-109e/6DNE	Ethernet	6	57	1	2	336x122x120	-
DN-109e/7SNE	Ethernet	7	57	1	1	382x122x120	-
DN-109e/7DNE	Ethernet	7	57	1	2	382x122x120	-
DN-109e/8SNE	Ethernet	8	57	1	1	430x122x120	-
DN-109e/8DNE	Ethernet	8	57	1	2	430x122x120	-
DN-109e/9SNE	Ethernet	9	57	1	1	478x122x120	-
DN-109e/9DNE	Ethernet	9	57	1	2	478x122x120	-
DN-109e/10SNE	Ethernet	10	57	1	1	526x122x120	-
DN-109e/10DNE	Ethernet	10	57	1	2	526x122x120	-

DN-109eNP		Digit of 57mm.		Profibus IP65			
DN-109e/3SNP	Profibus DP	3	57	1	1	210x130x120	-
DN-109e/4SNP	Profibus DP	4	57	1	1	288x130x120	-
DN-109e/4DNP	Profibus DP	4	57	1	2	288x130x120	-
DN-109e/5SNP	Profibus DP	5	57	1	1	288x130x120	-
DN-109e/5DNP	Profibus DP	5	57	1	2	288x130x120	-
DN-109e/6SNP	Profibus DP	6	57	1	1	336x130x120	-
DN-109e/6DNP	Profibus DP	6	57	1	2	336x130x120	-
DN-109e/7SNP	Profibus DP	7	57	1	1	382x130x120	-
DN-109e/7DNP	Profibus DP	7	57	1	2	382x130x120	-
DN-109e/8SNP	Profibus DP	8	57	1	1	430x130x120	-
DN-109e/8DNP	Profibus DP	8	57	1	2	430x130x120	-
DN-109e/9SNP	Profibus DP	9	57	1	1	478x130x120	-
DN-109e/9DNP	Profibus DP	9	57	1	2	478x130x120	-
DN-109e/10SNP	Profibus DP	10	57	1	1	526x130x120	-
DN-109e/10DNP	Profibus DP	10	57	1	2	526x130x120	-

DN-109eNW		Digit of 57mm.		Wifi. IP65			
DN-109e/3SNW	Wifi	3	57	1	1	210x122x120	-
DN-109e/4SNW	Wifi	4	57	1	1	288x122x120	-
DN-109e/4DNW	Wifi	4	57	1	2	288x122x120	-
DN-109e/5SNW	Wifi	5	57	1	1	288x122x120	-
DN-109e/5DNW	Wifi	5	57	1	2	288x122x120	-
DN-109e/6SNW	Wifi	6	57	1	1	336x122x120	-
DN-109e/6DNW	Wifi	6	57	1	2	336x122x120	-
DN-109e/7SNW	Wifi	7	57	1	1	382x122x120	-
DN-109e/7DNW	Wifi	7	57	1	2	382x122x120	-
DN-109e/8SNW	Wifi	8	57	1	1	430x122x120	-
DN-109e/8DNW	Wifi	8	57	1	2	430x122x120	-
DN-109e/9SNW	Wifi	9	57	1	1	478x122x120	-
DN-109e/9DNW	Wifi	9	57	1	2	478x122x120	-
DN-109e/10SNW	Wifi	10	57	1	1	526x122x120	-
DN-109e/10DNW	Wifi	10	57	1	2	526x122x120	-

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DN-109eAP		Digit of 57mm.		Analog input. IP65			
DN-109e/3SAP	Process	3	57	1	1	210x122x120	-
DN-109e/3DAP	Process	3	57	1	2	288x122x120	
DN-109e/4SAP	Process	4	57	1	1	288x122x120	-
DN-109e/4DAP	Process	4	57	1	2	288x122x120	
DN-109e/5SAP	Process	5	57	1	1	288x122x120	-
DN-109e/5DAP	Process	5	57	1	2	288x122x120	

DN-109eAT		Digit of 57mm.		Analog input. IP65			
DN-109e/3SAT	Temperature	3	57	1	1	210x122x120	-
DN-109e/3DAT	Temperature	3	57	1	2	288x122x120	
DN-109e/4SAT	Temperature	4	57	1	1	288x122x120	-
DN-109e/4DAT	Temperature	4	57	1	2	288x122x120	
DN-109e/5SAT	Temperature	5	57	1	1	288x122x120	-
DN-109e/5DAT	Temperature	5	57	1	2	288x122x120	

DN-109Ce/AP		57mm COLOR		Analog input. IP65			
DN-109Ce/3SAP	Process	3	57	1	1	210x122x120	-
DN-109Ce/3DAP	Process	3	57	1	2	288x122x120	
DN-109Ce/4SAP	Process	4	57	1	1	288x122x120	-
DN-109Ce/4DAP	Process	4	57	1	2	288x122x120	
DN-109Ce/5SAP	Process	5	57	1	1	288x122x120	-
DN-109Ce/5DAP	Process	5	57	1	2	288x122x120	

DN-109Ce/AT		57mm COLOR		Analog input. IP65			
DN-109Ce/3SAT	Temperature	3	57	1	1	210x122x120	-
DN-109Ce/3DAT	Temperature	3	57	1	2	288x122x120	
DN-109Ce/4SAT	Temperature	4	57	1	1	288x122x120	-
DN-109Ce/4DAT	Temperature	4	57	1	2	288x122x120	
DN-109Ce/5SAT	Temperature	5	57	1	1	288x122x120	-
DN-109Ce/5DAT	Temperature	5	57	1	2	288x122x120	

OPTION: POWER SUPPLY 24Vcc

S=1 Side

D= 2 Sides

DN-109e/ _APX	Serial line						To add
DN-109e/ _ATX	Serial line						To add

Option Text leds	Models S	+TL			1	+96mm	To add
Option Text vinyl	Models S	+TV			2	+96mm	To add
Option Text leds	Models D	+TL			1	+96mm	To add
Option Text vinyl	Models D	+TV			2	+96mm	To add

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr.	From PC
DN-119X	Digit of 100mm.		Repeater RS-232/RS485. INDOOR USE.					
DN-119/3SX	Serial	3	100	1	1	324x177x120	-	
DN-119/4SX	Serial	4	100	1	1	414x177x120	-	
DN-119/4DX	Serial	4	100	1	2	414x177x120	-	
DN-119/5SX	Serial	5	100	1	1	504x177x120	-	
DN-119/5DX	Serial	5	100	1	2	504x177x120	-	
DN-119/6SX	Serial	6	100	1	1	594x177x120	-	
DN-119/6DX	Serial	6	100	1	2	594x177x120	-	
DN-119/7SX	Serial	7	100	1	1	684x177x120	-	
DN-119/7DX	Serial	7	100	1	2	684x177x120	-	
DN-119/8SX	Serial	8	100	1	1	774x177x120	-	
DN-119/8DX	Serial	8	100	1	2	774x177x120	-	
DN-119/9SX	Serial	9	100	1	1	864x177x120	-	
DN-119/9DX	Serial	9	100	1	2	864x177x120	-	
DN-119/10SX	Serial	10	100	1	1	954x177x120	-	
DN-119/10DX	Serial	10	100	1	2	954x177x120	-	

DN-119P	Digit of 100mm.		Control Binary. INDOOR USE					
DN-119/3SP	Binary	3	100	1	1	324x177x120	-	
DN-119/4SP	Binary	4	100	1	1	414x177x120	-	
DN-119/4DP	Binary	4	100	1	2	414x177x120	-	
DN-119/5SP	Binary	5	100	1	1	504x177x120	-	
DN-119/5DP	Binary	5	100	1	2	504x177x120	-	
DN-119/6SP	Binary	6	100	1	1	594x177x120	-	
DN-119/6DP	Binary	6	100	1	2	594x177x120	-	
DN-119/7SP	Binary	7	100	1	1	684x177x120	-	
DN-119/7DP	Binary	7	100	1	2	684x177x120	-	
DN-119/8SP	Binary	8	100	1	1	774x177x120	-	
DN-119/8DP	Binary	8	100	1	2	774x177x120	-	
DN-119/9SP	Binary	9	100	1	1	864x177x120	-	
DN-119/9DP	Binary	9	100	1	2	864x177x120	-	
DN-119/10SP	Binary	10	100	1	1	954x177x120	-	
DN-119/10DP	Binary	10	100	1	2	954x177x120	-	

DN-119TH	Digit of 100mm.		Temperature and humidity. INDOOR USE					
DN-119/STH	Temp. and humid	5	100	1	1	504x177x120	-	
DN-119/DTH	Temp. and humid	5	100	1	2	504x177x120	-	

OPTION: POWER SUPPLY 24Vcc

Probe TH 2m

S=1 Side

D= 2 Sides

Opti. relays (PR)	To add						
Option Serial L.(PX)	To add						
Option Text leds	Models S	+TL				+180mm	
Option Text vinyl	Models S	+TV				+180mm	
Option Text leds	Models D	+TL				+180mm	
Option Text vinyl	Models D	+TV				+180mm	
Models PR =	Models P + Option relays						
Models PX =	Models P + Option serial line						
Models PXR =	Models P + Option serial line + Option relays						

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr.	From PC
DN-119NE	Digit of 100mm.		Ethernet. INDOOR					
DN-119/3SNE	Ethernet	3	100	1	1	324x177x120	-	-
DN-119/4SNE	Ethernet	4	100	1	1	414x177x120	-	-
DN-119/4DNE	Ethernet	4	100	1	2	414x177x120	-	-
DN-119/5SNE	Ethernet	5	100	1	1	504x177x120	-	-
DN-119/5DNE	Ethernet	5	100	1	2	504x177x120	-	-
DN-119/6SNE	Ethernet	6	100	1	1	594x177x120	-	-
DN-119/6DNE	Ethernet	6	100	1	2	594x177x120	-	-
DN-119/7SNE	Ethernet	7	100	1	1	684x177x120	-	-
DN-119/7DNE	Ethernet	7	100	1	2	684x177x120	-	-
DN-119/8SNE	Ethernet	8	100	1	1	774x177x120	-	-
DN-119/8DNE	Ethernet	8	100	1	2	774x177x120	-	-
DN-119/9SNE	Ethernet	9	100	1	1	864x177x120	-	-
DN-119/9DNE	Ethernet	9	100	1	2	864x177x120	-	-
DN-119/10SNE	Ethernet	10	100	1	1	954x177x120	-	-
DN-119/10DNE	Ethernet	10	100	1	2	954x177x120	-	-

DN-119NP	Digit of 100mm.		Profibus-DP. INDOOR					
DN-119/3SNP	Profibus-DP	3	100	1	1	324x177x120	-	-
DN-119/4SNP	Profibus-DP	4	100	1	1	414x177x120	-	-
DN-119/4DNP	Profibus-DP	4	100	1	2	414x177x120	-	-
DN-119/5SNP	Profibus-DP	5	100	1	1	504x177x120	-	-
DN-119/5DNP	Profibus-DP	5	100	1	2	504x177x120	-	-
DN-119/6SNP	Profibus-DP	6	100	1	1	594x177x120	-	-
DN-119/6DNP	Profibus-DP	6	100	1	2	594x177x120	-	-
DN-119/7SNP	Profibus-DP	7	100	1	1	684x177x120	-	-
DN-119/7DNP	Profibus-DP	7	100	1	2	684x177x120	-	-
DN-119/8SNP	Profibus-DP	8	100	1	1	774x177x120	-	-
DN-119/8DNP	Profibus-DP	8	100	1	2	774x177x120	-	-
DN-119/9SNP	Profibus-DP	9	100	1	1	864x177x120	-	-
DN-119/9DNP	Profibus-DP	9	100	1	2	864x177x120	-	-
DN-119/10SNP	Profibus-DP	10	100	1	1	954x177x120	-	-
DN-119/10DNP	Profibus-DP	10	100	1	2	954x177x120	-	-

DN-119NW	Digit of 100mm.		Wifi. INDOOR					
DN-119/3SNW	Wifi	3	100	1	1	324x177x120	-	-
DN-119/4SNW	Wifi	4	100	1	1	414x177x120	-	-
DN-119/4DNW	Wifi	4	100	1	2	414x177x120	-	-
DN-119/5SNW	Wifi	5	100	1	1	504x177x120	-	-
DN-119/5DNW	Wifi	5	100	1	2	504x177x120	-	-
DN-119/6SNW	Wifi	6	100	1	1	594x177x120	-	-
DN-119/6DNW	Wifi	6	100	1	2	594x177x120	-	-
DN-119/7SNW	Wifi	7	100	1	1	684x177x120	-	-
DN-119/7DNW	Wifi	7	100	1	2	684x177x120	-	-
DN-119/8SNW	Wifi	8	100	1	1	774x177x120	-	-
DN-119/8DNW	Wifi	8	100	1	2	774x177x120	-	-
DN-119/9SNW	Wifi	9	100	1	1	864x177x120	-	-
DN-119/9DNW	Wifi	9	100	1	2	864x177x120	-	-
DN-119/10SNW	Wifi	10	100	1	1	954x177x120	-	-
DN-119/10DNW	Wifi	10	100	1	2	954x177x120	-	-

Option Text leds	Models S	+TL				+180mm	
Option Text vinyl	Models S	+TV				+180mm	
Option Text leds	Models D	+TL				+180mm	
Option Text vinyl	Models D	+TV				+180mm	

OPTION: POWER SUPPLY 24Vcc

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DN-119AP	Digit of 100mm.		Analog input.	INDOOR			
DN-119/3SAP	Process	3	100	1	1	324x177x120	-
DN-119/3DAP	Process	3	100	1	2	324x177x120	
DN-119/4SAP	Process	4	100	1	1	414x177x120	-
DN-119/4DAP	Process	4	100	1	2	414x177x120	
DN-119/5SAP	Process	5	100	1	1	504x177x120	-
DN-119/5DAP	Process	5	100	1	2	504x177x120	

DN-119AT	Digit of 100mm.		Analog input.	INDOOR			
DN-119/3SAT	Temperature	3	100	1	1	324x177x120	-
DN-119/3DAT	Temperature	3	100	1	2	324x177x120	
DN-119/4SAT	Temperature	4	100	1	1	414x177x120	-
DN-119/4DAT	Temperature	4	100	1	2	414x177x120	
DN-119/5SAT	Temperature	5	100	1	1	504x177x120	-
DN-119/5DAT	Temperature	5	100	1	2	504x177x120	

OPTION: POWER SUPPLY 24Vcc

S=1 Side

D= 2 Sides

DN-119/ APX	Serial line						To add
DN-119/ ATX	Serial line						To add
DN-119/ APR	Output relays						To add
DN-119/ ATR	Output relays						To add
DN-119/ APXR	Serial line + relays						To add
DN-119/ ATXR	Serial line + relays						To add

Option Text leds	Models S	+TL			1	+180mm	To add
Option Text vinyl	Models S	+TV			2	+180mm	To add
Option Text leds	Models D	+TL			1	+180mm	To add
Option Text vinyl	Models D	+TV			2	+180mm	To add

MODEL	Control	Digits	Height character mm	Lines	Sides	Measures in mm	Progr.	From PC
DN-119eX	Digit of 100mm.		Repeater RS-232/RS485. IP65.					
DN-119e/3SX	Serial	3	100	1	1	324x177x120	-	-
DN-119e/4SX	Serial	4	100	1	1	414x177x120	-	-
DN-119e/4DX	Serial	4	100	1	2	414x177x120	-	-
DN-119e/5SX	Serial	5	100	1	1	504x177x120	-	-
DN-119e/5DX	Serial	5	100	1	2	504x177x120	-	-
DN-119e/6SX	Serial	6	100	1	1	594x177x120	-	-
DN-119e/6DX	Serial	6	100	1	2	594x177x120	-	-
DN-119e/7SX	Serial	7	100	1	1	684x177x120	-	-
DN-119e/7DX	Serial	7	100	1	2	684x177x120	-	-
DN-119e/8SX	Serial	8	100	1	1	774x177x120	-	-
DN-119e/8DX	Serial	8	100	1	2	774x177x120	-	-
DN-119e/9SX	Serial	9	100	1	1	864x177x120	-	-
DN-119e/9DX	Serial	9	100	1	2	864x177x120	-	-
DN-119e/10SX	Serial	10	100	1	1	954x177x120	-	-
DN-119e/10DX	Serial	10	100	1	2	954x177x120	-	-

DN-119eP	Digit of 100mm.		Control Binary. IP65					
DN-119e/3SP	Binary	3	100	1	1	324x177x120	-	-
DN-119e/4SP	Binary	4	100	1	1	414x177x120	-	-
DN-119e/4DP	Binary	4	100	1	2	414x177x120	-	-
DN-119e/5SP	Binary	5	100	1	1	504x177x120	-	-
DN-119e/5DP	Binary	5	100	1	2	504x177x120	-	-
DN-119e/6SP	Binary	6	100	1	1	594x177x120	-	-
DN-119e/6DP	Binary	6	100	1	2	594x177x120	-	-
DN-119e/7SP	Binary	7	100	1	1	684x177x120	-	-
DN-119e/7DP	Binary	7	100	1	2	684x177x120	-	-
DN-119e/8SP	Binary	8	100	1	1	774x177x120	-	-
DN-119e/8DP	Binary	8	100	1	2	774x177x120	-	-
DN-119e/9SP	Binary	9	100	1	1	864x177x120	-	-
DN-119e/9DP	Binary	9	100	1	2	864x177x120	-	-
DN-119e/10SP	Binary	10	100	1	1	954x177x120	-	-
DN-119e/10DP	Binary	10	100	1	2	954x177x120	-	-

DN-119eTH	Digit of 100mm.		Temperature and humidity. IP65					
DN-119e/STH	Temp. and humid	5	100	1	1	504x177x120	-	-
DN-119e/DTH	Temp. and humid	5	100	1	2	504x177x120	-	-

DN-119eNE	Digit of 100mm.		Ethernet IP65					
DN-119e/3SNE	Ethernet	3	100	1	1	324x177x120	-	-
DN-119e/4SNE	Ethernet	4	100	1	1	414x177x120	-	-
DN-119e/4DNE	Ethernet	4	100	1	2	414x177x120	-	-
DN-119e/5SNE	Ethernet	5	100	1	1	504x177x120	-	-
DN-119e/5DNE	Ethernet	5	100	1	2	504x177x120	-	-
DN-119e/6SNE	Ethernet	6	100	1	1	594x177x120	-	-
DN-119e/6DNE	Ethernet	6	100	1	2	594x177x120	-	-
DN-119e/7SNE	Ethernet	7	100	1	1	684x177x120	-	-
DN-119e/7DNE	Ethernet	7	100	1	2	684x177x120	-	-
DN-119e/8SNE	Ethernet	8	100	1	1	774x177x120	-	-
DN-119e/8DNE	Ethernet	8	100	1	2	774x177x120	-	-
DN-119e/9SNE	Ethernet	9	100	1	1	864x177x120	-	-
DN-119e/9DNE	Ethernet	9	100	1	2	864x177x120	-	-
DN-119e/10SNE	Ethernet	10	100	1	1	954x177x120	-	-
DN-119e/10DNE	Ethernet	10	100	1	2	954x177x120	-	-

OPTION: POWER SUPPLY 24Vcc
Probe TH 2m

S=1 Side	D= 2 Sides					
Opti. relays (PR)	To add					
Option Serial L.(PX)	To add					
Option Text leds	Models S	+TL				+180mm
Option Text vinyl	Models S	+TV				+180mm
Option Text leds	Models D	+TL				+180mm
Option Text vinyl	Models D	+TV				+180mm
Models PR =	Models P + Option relays					
Models PX =	Models P + Option serial line					
Models PXR =	Models P + Option serial line + Option relays					

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DN-119eNP	Digit of 100mm.		Profibus	IP65			
DN-119e/3SNP	Profibus DP	3	100	1	1	324x177x120	-
DN-119e/4SNP	Profibus DP	4	100	1	1	414x177x120	-
DN-119e/4DNP	Profibus DP	4	100	1	2	414x177x120	-
DN-119e/5SNP	Profibus DP	5	100	1	1	504x177x120	-
DN-119e/5DNP	Profibus DP	5	100	1	2	504x177x120	-
DN-119e/6SNP	Profibus DP	6	100	1	1	594x177x120	-
DN-119e/6DNP	Profibus DP	6	100	1	2	594x177x120	-
DN-119e/7SNP	Profibus DP	7	100	1	1	684x177x120	-
DN-119e/7DNP	Profibus DP	7	100	1	2	684x177x120	-
DN-119e/8SNP	Profibus DP	8	100	1	1	774x177x120	-
DN-119e/8DNP	Profibus DP	8	100	1	2	774x177x120	-
DN-119e/9SNP	Profibus DP	9	100	1	1	864x177x120	-
DN-119e/9DNP	Profibus DP	9	100	1	2	864x177x120	-
DN-119e/10SNP	Profibus DP	10	100	1	1	954x177x120	-
DN-119e/10DNP	Profibus DP	10	100	1	2	954x177x120	-

DN-119eNW	Digit of 100mm.		Wifi.	IP65			
DN-119e/3SNW	Wifi	3	100	1	1	324x177x120	-
DN-119e/4SNW	Wifi	4	100	1	1	414x177x120	-
DN-119e/4DNW	Wifi	4	100	1	2	414x177x120	-
DN-119e/5SNW	Wifi	5	100	1	1	504x177x120	-
DN-119e/5DNW	Wifi	5	100	1	2	504x177x120	-
DN-119e/6SNW	Wifi	6	100	1	1	594x177x120	-
DN-119e/6DNW	Wifi	6	100	1	2	594x177x120	-
DN-119e/7SNW	Wifi	7	100	1	1	684x177x120	-
DN-119e/7DNW	Wifi	7	100	1	2	684x177x120	-
DN-119e/8SNW	Wifi	8	100	1	1	774x177x120	-
DN-119e/8DNW	Wifi	8	100	1	2	774x177x120	-
DN-119e/9SNW	Wifi	9	100	1	1	864x177x120	-
DN-119e/9DNW	Wifi	9	100	1	2	864x177x120	-
DN-119e/10SNW	Wifi	10	100	1	1	954x177x120	-
DN-119e/10DNW	Wifi	10	100	1	2	954x177x120	-

Option Text leds	Models S	+TL				+180mm	
Option Text vinyl	Models S	+TV				+180mm	
Option Text leds	Models D	+TL				+180mm	
Option Text vinyl	Models D	+TV				+180mm	

OPTION: POWER SUPPLY 24Vcc

DN-119eAP	Digit of 100mm.		Analog input.	IP65			
DN-119e/3SAP	Process	3	100	1	1	324x177x120	-
DN-119e/3DAP	Process	3	100	1	2	324x177x120	-
DN-119e/4SAP	Process	4	100	1	1	414x177x120	-
DN-119e/4DAP	Process	4	100	1	2	414x177x120	-
DN-119e/5SAP	Process	5	100	1	1	504x177x120	-
DN-119e/5DAP	Process	5	100	1	2	504x177x120	-

DN-119eAT	Digit of 100mm.		Analog input.	IP65			
DN-119e/3SAT	Temperature	3	100	1	1	324x177x120	-
DN-119e/3DAT	Temperature	3	100	1	2	324x177x120	-
DN-119e/4SAT	Temperature	4	100	1	1	414x177x120	-
DN-119e/4DAT	Temperature	4	100	1	2	414x177x120	-
DN-119e/5SAT	Temperature	5	100	1	1	504x177x120	-
DN-119e/5DAT	Temperature	5	100	1	2	504x177x120	-

S=1 Side

D= 2 Sides

DN-119e/ _APX	Serial line						To add
DN-119e/ _ATX	Serial line						To add
DN-119e/ _APR	Sortida reles						Afegir
DN-119e/ _ATR	Sortida reles						Afegir
DN-119e/ _APXR	Linia serie + reles						Afegir
DN-119e/ _ATXR	Linia serie + reles						Afegir
Option Text leds	Models S	+TL			1	+180mm	To add
Option Text vinyl	Models S	+TV			2	+180mm	To add
Option Text leds	Models D	+TL			1	+180mm	To add
Option Text vinyl	Models D	+TV			2	+180mm	To add

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DN-119ehX	Digit of 100mm.	Repeater RS-232/RS485. OUTDOOR USE.					
DN-119eh/3SX	Serial	3	100	1	1	324x177x120	-
DN-119eh/4SX	Serial	4	100	1	1	414x177x120	-
DN-119eh/4DX	Serial	4	100	1	2	414x177x120	-
DN-119eh/5SX	Serial	5	100	1	1	504x177x120	-
DN-119eh/5DX	Serial	5	100	1	2	504x177x120	-
DN-119eh/6SX	Serial	6	100	1	1	594x177x120	-
DN-119eh/6DX	Serial	6	100	1	2	594x177x120	-
DN-119eh/7SX	Serial	7	100	1	1	684x177x120	-
DN-119eh/7DX	Serial	7	100	1	2	684x177x120	-
DN-119eh/8SX	Serial	8	100	1	1	774x177x120	-
DN-119eh/8DX	Serial	8	100	1	2	774x177x120	-
DN-119eh/9SX	Serial	9	100	1	1	864x177x120	-
DN-119eh/9DX	Serial	9	100	1	2	864x177x120	-
DN-119eh/10SX	Serial	10	100	1	1	954x177x120	-
DN-119eh/10DX	Serial	10	100	1	2	954x177x120	-

DN-119ehP	Digit of 100mm.	Control Binary. OUTDOOR USE					
DN-119eh/3SP	Binary	3	100	1	1	324x177x120	-
DN-119eh/4SP	Binary	4	100	1	1	414x177x120	-
DN-119eh/4DP	Binary	4	100	1	2	414x177x120	-
DN-119eh/5SP	Binary	5	100	1	1	504x177x120	-
DN-119eh/5DP	Binary	5	100	1	2	504x177x120	-
DN-119eh/6SP	Binary	6	100	1	1	594x177x120	-
DN-119eh/6DP	Binary	6	100	1	2	594x177x120	-
DN-119eh/7SP	Binary	7	100	1	1	684x177x120	-
DN-119eh/7DP	Binary	7	100	1	2	684x177x120	-
DN-119eh/8SP	Binary	8	100	1	1	774x177x120	-
DN-119eh/8DP	Binary	8	100	1	2	774x177x120	-
DN-119eh/9SP	Binary	9	100	1	1	864x177x120	-
DN-119eh/9DP	Binary	9	100	1	2	864x177x120	-
DN-119eh/10SP	Binary	10	100	1	1	954x177x120	-
DN-119eh/10DP	Binary	10	100	1	2	954x177x120	-

DN-119ehTH	Digit of 100mm.	Temperature and humidity. OUTDOOR USE					
DN-119eh/STH	Temp. and humid	5	100	1	1	504x177x120	-
DN-119eh/DTH	Temp. and humid	5	100	1	2	504x177x120	-

DN-119ehNE	Digit of 100mm.	Ethernet. OUTDOOR					
DN-119eh/3SNE	Ethernet	3	100	1	1	324x177x120	-
DN-119eh/4SNE	Ethernet	4	100	1	1	414x177x120	-
DN-119eh/4DNE	Ethernet	4	100	1	2	414x177x120	-
DN-119eh/5SNE	Ethernet	5	100	1	1	504x177x120	-
DN-119eh/5DNE	Ethernet	5	100	1	2	504x177x120	-
DN-119eh/6SNE	Ethernet	6	100	1	1	594x177x120	-
DN-119eh/6DNE	Ethernet	6	100	1	2	594x177x120	-
DN-119eh/7SNE	Ethernet	7	100	1	1	684x177x120	-
DN-119eh/7DNE	Ethernet	7	100	1	2	684x177x120	-
DN-119eh/8SNE	Ethernet	8	100	1	1	774x177x120	-
DN-119eh/8DNE	Ethernet	8	100	1	2	774x177x120	-
DN-119eh/9SNE	Ethernet	9	100	1	1	864x177x120	-
DN-119eh/9DNE	Ethernet	9	100	1	2	864x177x120	-
DN-119eh/10SNE	Ethernet	10	100	1	1	954x177x120	-
DN-119eh/10DNE	Ethernet	10	100	1	2	954x177x120	-

OPTION: POWER SUPPLY 24Vcc

Probe TH 2m

S=1 Side

D= 2 Sides

Opti. relays (PR)	To add					
Option Serial L.(PX)	To add					
Option Text leds	Models S	+TL				+180mm
Option Text vinyl	Models S	+TV				+180mm
Option Text leds	Models D	+TL				+180mm
Option Text vinyl	Models D	+TV				+180mm
Models PR =	Models P + Option relays					
Models PX =	Models P + Option serial line					
Models PXR =	Models P + Option serial line + Option relays					

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr.	From PC
DN-119ehNP	Digit of 100mm.		Profibus-DP.			OUTDOOR		
DN-119eh/3SNP	Profibus DP	3	100	1	1	324x177x120	-	
DN-119eh/4SNP	Profibus DP	4	100	1	1	414x177x120	-	
DN-119eh/4DNP	Profibus DP	4	100	1	2	414x177x120	-	
DN-119eh/5SNP	Profibus DP	5	100	1	1	504x177x120	-	
DN-119eh/5DNP	Profibus DP	5	100	1	2	504x177x120	-	
DN-119eh/6SNP	Profibus DP	6	100	1	1	594x177x120	-	
DN-119eh/6DNP	Profibus DP	6	100	1	2	594x177x120	-	
DN-119eh/7SNP	Profibus DP	7	100	1	1	684x177x120	-	
DN-119eh/7DNP	Profibus DP	7	100	1	2	684x177x120	-	
DN-119eh/8SNP	Profibus DP	8	100	1	1	774x177x120	-	
DN-119eh/8DNP	Profibus DP	8	100	1	2	774x177x120	-	
DN-119eh/9SNP	Profibus DP	9	100	1	1	864x177x120	-	
DN-119eh/9DNP	Profibus DP	9	100	1	2	864x177x120	-	
DN-119eh/10SNP	Profibus DP	10	100	1	1	954x177x120	-	
DN-119eh/10DNP	Profibus DP	10	100	1	2	954x177x120	-	

DN-119ehNW	Digit of 100mm.		Wifi.			OUTDOOR		
DN-119eh/3SNW	Wifi	3	100	1	1	324x177x120	-	
DN-119eh/4SNW	Wifi	4	100	1	1	414x177x120	-	
DN-119eh/4DNW	Wifi	4	100	1	2	414x177x120	-	
DN-119eh/5SNW	Wifi	5	100	1	1	504x177x120	-	
DN-119eh/5DNW	Wifi	5	100	1	2	504x177x120	-	
DN-119eh/6SNW	Wifi	6	100	1	1	594x177x120	-	
DN-119eh/6DNW	Wifi	6	100	1	2	594x177x120	-	
DN-119eh/7SNW	Wifi	7	100	1	1	684x177x120	-	
DN-119eh/7DNW	Wifi	7	100	1	2	684x177x120	-	
DN-119eh/8SNW	Wifi	8	100	1	1	774x177x120	-	
DN-119eh/8DNW	Wifi	8	100	1	2	774x177x120	-	
DN-119eh/9SNW	Wifi	9	100	1	1	864x177x120	-	
DN-119eh/9DNW	Wifi	9	100	1	2	864x177x120	-	
DN-119eh/10SNW	Wifi	10	100	1	1	954x177x120	-	
DN-119eh/10DNW	Wifi	10	100	1	2	954x177x120	-	

Option Text leds	Models S	+TL				+180mm	
Option Text vinyl	Models S	+TV				+180mm	
Option Text leds	Models D	+TL				+180mm	
Option Text vinyl	Models D	+TV				+180mm	

OPTION: POWER SUPPLY 24Vcc

DN-119ehAP	Digit of 100mm.		Analog input.			OUTDOOR		
DN-119eh/3SAP	Process	3	100	1	1	324x177x120	-	
DN-119eh/3DAP	Process	3	100	1	2	324x177x120	-	
DN-119eh/4SAP	Process	4	100	1	1	414x177x120	-	
DN-119eh/4DAP	Process	4	100	1	2	414x177x120	-	
DN-119eh/5SAP	Process	5	100	1	1	504x177x120	-	
DN-119eh/5DAP	Process	5	100	1	2	504x177x120	-	

DN-119ehAT	Digit of 100mm.		Analog input.			OUTDOOR		
DN-119eh/3SAT	Temperature	3	100	1	1	324x177x120	-	
DN-119eh/3DAT	Temperature	3	100	1	2	324x177x120	-	
DN-119eh/4SAT	Temperature	4	100	1	1	414x177x120	-	
DN-119eh/4DAT	Temperature	4	100	1	2	414x177x120	-	
DN-119eh/5SAT	Temperature	5	100	1	1	504x177x120	-	
DN-119eh/5DAT	Temperature	5	100	1	2	504x177x120	-	

S=1 Side

D= 2 Sides

DN-119eh/ __APX	Serial line						To add
DN-119eh/ __ATX	Serial line						To add
DN-119eh/ __APR	Sortida reles						Afegir
DN-119eh/ __ATR	Sortida reles						Afegir
DN-119eh/ __APXR	Linia serie + reles						Afegir
DN-119eh/ __ATXR	Linia serie + reles						Afegir
Option Text leds	Models S	+TL			1	+180mm	To add
Option Text vinyl	Models S	+TV			2	+180mm	To add
Option Text leds	Models D	+TL			1	+180mm	To add
Option Text vinyl	Models D	+TV			2	+180mm	To add

MODEL	Control	Digits	Height character mm	Lines	Sides	Measures in mm	Progr.	From PC
DN-129X	Digit of 250mm.		Repeater RS-232/RS485. INDOOR USE.					
DN-129/2SX	Serial	2	250	1	1	515x366x120	-	
DN-129/2DX	Serial	2	250	1	2	515x366x120	-	
DN-129/3SX	Serial	3	250	1	1	750x366x120	-	
DN-129/3DX	Serial	3	250	1	2	750x366x120	-	
DN-129/4SX	Serial	4	250	1	1	985x366x120	-	
DN-129/4DX	Serial	4	250	1	2	985x366x120	-	
DN-129/5SX	Serial	5	250	1	1	1220x366x120	-	
DN-129/5DX	Serial	5	250	1	2	1220x366x120	-	
DN-129/6SX	Serial	6	250	1	1	1455x366x120	-	
DN-129/6DX	Serial	6	250	1	2	1455x366x120	-	
DN-129/7SX	Serial	7	250	1	1	1690x366x120	-	
DN-129/7DX	Serial	7	250	1	2	1690x366x120	-	
DN-129/8SX	Serial	8	250	1	1	1925x366x120	-	
DN-129/8DX	Serial	8	250	1	2	1925x366x120	-	
DN-129/9SX	Serial	9	250	1	1	2160x366x120	-	
DN-129/9DX	Serial	9	250	1	2	2160x366x120	-	
DN-129/10SX	Serial	10	250	1	1	2395x366x120	-	
DN-129/10DX	Serial	10	250	1	2	2395x366x120	-	

DN-129P	Digit of 250mm.		Control Binary. INDOOR USE					
DN-129/2SP	Binary	2	250	1	1	515x366x120	-	
DN-129/2DP	Binary	2	250	1	2	515x366x120	-	
DN-129/3SP	Binary	3	250	1	1	750x366x120	-	
DN-129/3DP	Binary	3	250	1	2	750x366x120	-	
DN-129/4SP	Binary	4	250	1	1	985x366x120	-	
DN-129/4DP	Binary	4	250	1	2	985x366x120	-	
DN-129/5SP	Binary	5	250	1	1	1220x366x120	-	
DN-129/5DP	Binary	5	250	1	2	1220x366x120	-	
DN-129/6SP	Binary	6	250	1	1	1455x366x120	-	
DN-129/6DP	Binary	6	250	1	2	1455x366x120	-	
DN-129/7SP	Binary	7	250	1	1	1690x366x120	-	
DN-129/7DP	Binary	7	250	1	2	1690x366x120	-	
DN-129/8SP	Binary	8	250	1	1	1925x366x120	-	
DN-129/8DP	Binary	8	250	1	2	1925x366x120	-	
DN-129/9SP	Binary	9	250	1	1	2160x366x120	-	
DN-129/9DP	Binary	9	250	1	2	2160x366x120	-	
DN-129/10SP	Binary	10	250	1	1	2395x366x120	-	
DN-129/10DP	Binary	10	250	1	2	2395x366x120	-	

DN-129TH	Digit of 250mm.		Temperature and humidity. INDOOR USE					
DN-129/STH	Temp. and humid	5	250	1	1	1220x366x120	-	
DN-129/DTH	Temp. and humid	5	250	1	2	1220x366x120	-	

OPTION: POWER SUPPLY 24Vcc

Probe TH 2m

S=1 Side

D= 2 Sides

Opti. relays (PR)	To add							
Option Serial L.(PX)	To add							
Option Text vinyl	Models S	+TV			1			To add
Option Text vinyl	Models D	+TV			2			To add
Models PR =	Models P + Option relays							
Models PX =	Models P + Option serial line							
Models PXR =	Models P + Option serial line + Option relays							

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC	
DN-129NE	Digit of 250mm.		Ethernet. INDOOR					
DN-129/2SNE	Ethernet	2	250	1	1	515x366x120	-	
DN-129/2DNE	Ethernet	2	250	1	2	515x366x120	-	
DN-129/3SNE	Ethernet	3	250	1	1	750x366x120	-	
DN-129/3DNE	Ethernet	3	250	1	2	750x366x120	-	
DN-129/4SNE	Ethernet	4	250	1	1	985x366x120	-	
DN-129/4DNE	Ethernet	4	250	1	2	985x366x120	-	
DN-129/5SNE	Ethernet	5	250	1	1	1220x366x120	-	
DN-129/5DNE	Ethernet	5	250	1	2	1220x366x120	-	
DN-129/6SNE	Ethernet	6	250	1	1	1455x366x120	-	
DN-129/6DNE	Ethernet	6	250	1	2	1455x366x120	-	
DN-129/7SNE	Ethernet	7	250	1	1	1690x366x120	-	
DN-129/7DNE	Ethernet	7	250	1	2	1690x366x120	-	
DN-129/8SNE	Ethernet	8	250	1	1	1925x366x120	-	
DN-129/8DNE	Ethernet	8	250	1	2	1925x366x120	-	
DN-129/9SNE	Ethernet	9	250	1	1	2160x366x120	-	
DN-129/9DNE	Ethernet	9	250	1	2	2160x366x120	-	
DN-129/10SNE	Ethernet	10	250	1	1	2395x366x120	-	
DN-129/10DNE	Ethernet	10	250	1	2	2395x366x120	-	

DN-129NP	Digit of 250mm.		Profibus-DP. INDOOR					
DN-129/2SNP	Profibus-DP	2	250	1	1	515x366x120	-	
DN-129/2DNP	Profibus-DP	2	250	1	2	515x366x120	-	
DN-129/3SNP	Profibus-DP	3	250	1	1	750x366x120	-	
DN-129/3DNP	Profibus-DP	3	250	1	2	750x366x120	-	
DN-129/4SNP	Profibus-DP	4	250	1	1	985x366x120	-	
DN-129/4DNP	Profibus-DP	4	250	1	2	985x366x120	-	
DN-129/5SNP	Profibus-DP	5	250	1	1	1220x366x120	-	
DN-129/5DNP	Profibus-DP	5	250	1	2	1220x366x120	-	
DN-129/6SNP	Profibus-DP	6	250	1	1	1455x366x120	-	
DN-129/6DNP	Profibus-DP	6	250	1	2	1455x366x120	-	
DN-129/7SNP	Profibus-DP	7	250	1	1	1690x366x120	-	
DN-129/7DNP	Profibus-DP	7	250	1	2	1690x366x120	-	
DN-129/8SNP	Profibus-DP	8	250	1	1	1925x366x120	-	
DN-129/8DNP	Profibus-DP	8	250	1	2	1925x366x120	-	
DN-129/9SNP	Profibus-DP	9	250	1	1	2160x366x120	-	
DN-129/9DNP	Profibus-DP	9	250	1	2	2160x366x120	-	
DN-129/10SNP	Profibus-DP	10	250	1	1	2395x366x120	-	
DN-129/10DNP	Profibus-DP	10	250	1	2	2395x366x120	-	

DN-129NW	Digit of 250mm.		Wifi. INDOOR					
DN-129/2SNW	Wifi	2	250	1	1	515x366x120	-	
DN-129/2DNW	Wifi	2	250	1	2	515x366x120	-	
DN-129/3SNW	Wifi	3	250	1	1	750x366x120	-	
DN-129/3DNW	Wifi	3	250	1	2	750x366x120	-	
DN-129/4SNW	Wifi	4	250	1	1	985x366x120	-	
DN-129/4DNW	Wifi	4	250	1	2	985x366x120	-	
DN-129/5SNW	Wifi	5	250	1	1	1220x366x120	-	
DN-129/5DNW	Wifi	5	250	1	2	1220x366x120	-	
DN-129/6SNW	Wifi	6	250	1	1	1455x366x120	-	
DN-129/6DNW	Wifi	6	250	1	2	1455x366x120	-	
DN-129/7SNW	Wifi	7	250	1	1	1690x366x120	-	
DN-129/7DNW	Wifi	7	250	1	2	1690x366x120	-	
DN-129/8SNW	Wifi	8	250	1	1	1925x366x120	-	
DN-129/8DNW	Wifi	8	250	1	2	1925x366x120	-	
DN-129/9SNW	Wifi	9	250	1	1	2160x366x120	-	
DN-129/9DNW	Wifi	9	250	1	2	2160x366x120	-	
DN-129/10SNW	Wifi	10	250	1	1	2395x366x120	-	
DN-129/10DNW	Wifi	10	250	1	2	2395x366x120	-	

MODEL	Control	Digits	Heigh character mm	Lines	Sides	Measures in mm	Progr. From PC
DN-129AP	Digit of 250mm.		Analog input. INDOOR				
DN-129/3SAP	Process	3	250	1	1	750x366x120	-
DN-129/3DAP	Process	3	250	1	2	750x366x120	
DN-129/4SAP	Process	4	250	1	1	985x366x120	-
DN-129/4DAP	Process	4	250	1	2	985x366x120	
DN-129/5SAP	Process	5	250	1	1	1220x366x120	-
DN-129/5DAP	Process	5	250	1	2	1220x366x120	

DN-129AT	Digit of 250mm.		Analog input. INDOOR				
DN-129/3SAT	Temperature	3	250	1	1	750x366x120	-
DN-129/3DAT	Temperature	3	250	1	2	750x366x120	
DN-129/4SAT	Temperature	4	250	1	1	985x366x120	-
DN-129/4DAT	Temperature	4	250	1	2	985x366x120	
DN-129/5SAT	Temperature	5	250	1	1	1220x366x120	-
DN-129/5DAT	Temperature	5	250	1	2	1220x366x120	

OPTION: POWER SUPPLY 24Vcc

S=1 Side

D= 2 Sides

DN-129/ APX	Serial line						To add
DN-129/ ATX	Serial line						To add
DN-129/ APR	Output relays						To add
DN-129/ ATR	Output relays						To add
DN-129/ APXR	Serial line + relays						To add
DN-129/ ATXR	Serial line + relays						To add

Option Text vinyl	Models S	+TV			1		To add
Option Text vinyl	Models D	+TV			2		To add

DR-105	Clock Indoor						
	RDS Receiver	Temp. + hum.					
DR-105	No	No	50	No		240x120x60	
DR-105/A	Yes	No	50	No		240x120x60	
DR-105/TH	No	Yes	50	No		240x120x60	
DR-105/X	No	No	50	Yes		240x120x60	
DR-105/ATH	Yes	Yes	50	No		240x120x60	
DR-105/AX	Yes	No	50	Yes		240x120x60	
DR-105/THX	No	Yes	50	Yes		240x120x60	
DR-105/ATHX	Yes	Yes	50	Yes		240x120x60	

DR-105e	Clock Outdoor (IP-65)						
	RDS Receiver	Temp. + hum.					
DR-105e	No	No	50	No		240x120x60	
DR-105e/A	Yes	No	50	No		240x120x60	
DR-105e/TH	No	Yes	50	No		240x120x60	
DR-105e/X	No	No	50	Yes		240x120x60	
DR-105e/ATH	Yes	Yes	50	No		240x120x60	
DR-105e/AX	Yes	No	50	Yes		240x120x60	
DR-105e/THX	No	Yes	50	Yes		240x120x60	
DR-105e/ATHX	Yes	Yes	50	Yes		240x120x60	